Subject Index for
Electronics and Communications in Japan, Part II, Volume 75, 1992

10 Gbit/s: **6**, 13-23
180 degree hybrid coupler: **1**, 11-20
3-D VLSI: **5**, 103-116
64 K x 1: **4**, 61-72
A/D conversion: **2**, 1-11
Absorbing-type modulator: **6**, 24-32
Access time: **4**, 86-97
Acidic electrolyte: **10**, 67-74
Activation energy for nuclei growth: **2**, 79-89
Activation process: **7**, 60-67
Active pull-down circuit: **8**, 72-82
Address skew: **4**, 86-97
Adsorptive media: **4**, 1-17
Al-Nb alloy: **7**, 60-67
AlGaAs: **5**, 25-33
Amplitude-stabilizing circuits: **11**, 62-70
Analog IC circuits and theory: **4**, 107-118
Analysis: **9**, 63-71
Anisotropy: **7**, 19-31; **11**, 91-101
Anodized silicon: **7**, 68-74
Anti-reflection film: **1**, 56-63
Antireflective coating: **7**, 84-91
Arc discharge: **11**, 71-80
Arc light: **9**, 108-114
Arc phenomenon: **9**, 108-114
Area-time complexity: **2**, 101-113
ASIC: **12**, 67-76
Associative memory: **3**, 89-96
Attenuation: **9**, 80-90
Autogain control circuit: **4**, 98-106
Automatic gain control circuits: **11**, 62-70
Avalanche current: **8**, 63-71
Backpropagation: **11**, 11-19
Beam scanning: **11**, 32-41
Beam wave: **5**, 34-43
Beam-propagation method: **9**, 54-62
Bent fiber light injection: **4**, 43-51
Bi-Ti oxide ribbon: **2**, 90-100
BiCMOS: **1**, 77-85, 86-95; **4**, 61-72; **5**, 89-103; **12**, 77-87
Binary logic: **3**, 89-96
Bipolar: **1**, 77-85; **8**, 72-82; **12**, 77-87
Bipolar peripheral circuit: **3**, 97-108
Bipolar SRAM: **4**, 86-97
Bipolar transistor: **4**, 107-118
Bipolar-CMOS (BiCMOS) technology: **3**, 41-51
Black and white representation: **8**, 104-114
Bleaching: **5**, 25-33
Blocking gain: **10**, 75-83
Blue-shift: **4**, 27-36
Bonding pad region: **6**, 24-32
Čerenkov laser: **10**, 1-11
CAD: **11**, 51-61
Carbon black: **3**, 109-116
Carrier-trapping effect: **6**, 43-52
Cascade amplifier: **5**, 89-103
CCD sensor: **9**, 108-114
CDE: **2**, 72-78
CdTe modulator: **8**, 32-43
Channel capacity: **7**, 1-10
Channel impunity profile: **1**, 105-112
Characteristic impedance: **5**, 54-66
Chemical beam epitaxy: **9**, 101-107
Chiral materials: **9**, 34-43
Chirp function: **5**, 1-11
Chromium plating: **2**, 61-71
Circuit design: **6**, 89-100
CMOS: **1**, 86-95; CMOS: **11**, 102-107; **12**, 77-87
CMOS circuits: **1**, 64-76
CMOS rewrite amplifier: **5**, 89-103
CMOS-LSI: **11**, 51-61
Coherent detection imaging: **4**, 1-17
Collector-dotting circuit: **3**, 97-108
Common-frequency optical devices (COCA): **4**, 37-42
Complex ray analysis: **5**, 34-43
Composite materials: **3**, 109-116
Computer architecture: **2**, 28-43
Computer tomography imaging: **4**, 1-17
Conductor loss: **9**, 80-90
Conjugate gradient method: **9**, 25-33
Connection loss: **3**, 27-40
Contact reliability: **2**, 61-71
Contact resonance: **2**, 61-71
Convolver: **12**, 21-33
Core loss: **9**, 91-100
Correlative matrix: **3**, 89-96
Coupling: **3**, 1-8
CR oscillator: **4**, 98-106
Cross couple: **4**, 61-72
Crosstalk: **8**, 23-31
Crosstalk: **12**, 1-11
Crystallization: **2**, 90-100
Current conveyers: **1**, 43-55
Current distribution: **11**, 71-80; **11**, 81-90
Cylindrical structure: **10**, 1-11
Damping phenomenon: **6**, 13-23
Data line voltage: **5**, 89-103
DC drift: **6**, 76-88

Device simulation: **10**, 75-83
Dielectric constant: **2**, 90-100
Dielectric loaded waveguide: **7**, 92-102
Dielectric multilayer reflector: **2**, 12-19
Dielectric properties: **3**, 109-116
Dielectric resonator: **9**, 63-71
Dielectric strength: **2**, 90-100
Dielectric waveguide: **7**, 11-18
Diffusion furnace: **7**, 75-83
Digital neural chip: **2**, 44-60
Digital signal processing: **2**, 1-11
Direct address input method: **5**, 67-79
Direct drive motor: **1**, 56-63
Direct lithography: **11**, 51-61
Direct overwrite: **7**, 103-112
Direct-sensing circuit: **5**, 89-103
Directional anisotropy of hydrogen movement: **2**, 79-89
Distributed feedback: **6**, 13-23
Distributed parameter circuit model: **8**, 44-53
Driving method: **11**, 1-10
DSA MOS transistor: **1**, 105-112
Dual-gate FET: **1**, 11-20
Dual-mode pull-in technique: **3**, 41-51
Dye laser: **4**, 18-62
Dye-doped polymer: **12**, 50-56
Dynamic RAM: **8**, 54-62
ECL: **1**, 86-95; **12**, 77-87
ECL interface: **5**, 89-103
ECL RAM: **4**, 61-72
Eddy current loss: **9**, 91-100
EEPROM: **4**, 52-60l **10**, 93-103; **12**, 67-76
Eigenstate calculation: **2**, 20-27
Electrical conduction: **3**, 109-116
Electrical contact: **9**, 108-114; **11**, 71-80
Electroacoustic effect: **12**, 21-33
Electrochromism: **10**, 67-74
Electromagnetic field analysis: **6**, 89-100; **9**, 1-13
Electron beam: **11**, 51-61
Electron capacitance: **1**, 105-112
Electron wave: **9**, 44-53
Electrooptic modulator/deflector: **5**, 12-24
Electrooptical control device: **12**, 12-20
Electrostatic recording apparatus: **10**, 84-92
Embryonic nuclei: **2**, 79-89
Epitaxial crystal growth techniques: **2**, 20-27
Epitaxial growth: **12**, 97-104
Epoxy resin: **3**, 109-116
Equivalent circuit model: **6**, 76-88
Equivalent network approach: **9**, 44-53
Er-doped fiber: **4**, 37-42
Erasability: **7**, 103-112
Erbium optical amplifiers: **8**, 1-13
Erbium-doped silica fibers: **8**, 14-22
Error-correcting code: **4**, 73-85
Evaluation of film quality: **2**, 79-89
Evaluation test program: **5**, 80-88
Excitation absorption: **6**, 24-32
Exciton: **5**, 25-33
Exciton: **11**, 42-50
Expandable function: **12**, 57-66
Far-field image: **5**, 1-11
Fast division: **12**, 57-66
Fast Fourier transform: **2**, 1-11
Fast pull-in technique: **3**, 41-51
FD-TD method: **6**, 89-100
FEM: **11**, 91-101
Femtosecond pulse: **4**, 18-62
Ferroelectric liquid crystal cell: **6**, 33-42
Ferroelectronics: **2**, 90-100
FFT circuit: **5**, 103-116
Fiber optics: **8**, 23-31
Finite element method: **1**, 96-104; **7**, 92-102; **12**, 34-39
Finite periodic structure: **9**, 25-33
Finite-difference method: **1**, 21-31
Floating dust: **6**, 53-64
Flow sensors: **1**, 32-42
Force-displacement curve: **1**, 96-104
Frame rate control method: **10**, 104-112
Frequency conversion: **3**, 20-26
Frequency dependence: **11**, 71-80; **11**, 81-90
Frequency-shifted output: **8**, 32-43
Fresnel equation: **6**, 1-12
Fringe shift: **11**, 32-41
GaAs: **5**, 25-33
GaAs semiconductor: **12**, 21-33
$GaAs_{1-x}P_x$: **12**, 97-104
GaInAs/InP: **9**, 101-107
Gas flow: **1**, 32-42
Gate capacitance: **1**, 105-112
Gate delay time: **1**, 77-85
Geometrical optics: **5**, 34-43; **9**, 72-79
Grain-boundary traps: **7**, 51-59
Granular metallic film: **6**, 65-75
Gray scale: **10**, 104-112
Guided Waves: **1**, 1-10
Gummel-Poon model: **1**, 77-85
Head wear: **11**, 91-101
Hexagonal edge elements: **9**, 1-13
High density: **2**, 90-100
High resolution printing: **6**, 101-111
High speed printing: **6**, 101-111
High temperatures: **4**, 107-118
High temperature operation: **8**, 44-53
High-frequency magnetization: **9**, 91-100
High-order sampling: **2**, 1-11
High-purity silicon crystal: **10**, 75-83
High-speed bipolar decoding: **3**, 97-108
High-speed communication: **7**, 1-10

High-speed demodulation: **3**, 20-26
High-speed fuzzy interference: **3**, 52-64
High-speed modulation: **3**, 9-19; **6**, 13-23
High-speed printing: **10**, 84-92
High-speed SRAM: **3**, 97-108
High-speed scanning: **5**, 1-11
High-speed switching: **4**, 27-36
High-transmission state: **6**, 33-42
Hole capacitance: **1**, 105-112
Holographic stereogram: **7**, 41-50
Hybrid-type optical bistability: **12**, 50-56
Hydrogenated amorphous silicon films: **2**, 79-89
I-V characteristics: **2**, 72-78
I/O lines: **5**, 89-103
IC fabrication: **1**, 43-55
If-then fuzzy rule: **3**, 52-64
In-use lines: **4**, 43-51
Independent neural nets: **3**, 52-64
Index matching material: **3**, 27-40
Indirect address method: **5**, 67-79
Inductance: **11**, 71-80; **11**, 81-90
Inductive window: **9**, 14-24
Infinite magnetostatic field: **10**, 1-11
Information storage/delivery systems: **4**, 73-85
Infrared spectrometer: **7**, 32-40
InGaAsP/InP: **12**, 1-11
Inhomogeneous medium: **5**, 34-43; **9**, 72-79
Injection efficiency: **4**, 43-51
Intelligent sensor: **3**, 52-64
Interference barrier model: **2**, 79-89
Internal address latch: **4**, 86-97
Internal modulation: **8**, 32-43
Intracavity SGH: **6**, 1-12
Inverted slot line: **12**, 12-20
Ion beam sputter method: **12**, 97-104
John's matrix: **6**, 1-12
Junctions: **7**, 11-18
Kerr effect: **12**, 50-56
Keyboard switches: **1**, 96-104
Kirk effect: **1**, 77-85
KTP (K-TiO phosphate) crystal: **6**, 1-12
LAMIPOL: **6**, 65-75
Lagrange multipliers: **9**, 1-13
Laminated polarizer: **6**, 65-75
Lanthanide-diphthalocyanine: **10**, 67-74
Laser array: **11**, 32-41
Latch-up: **8**, 54-62
Latch-up characteristics: **1**, 86-95
Lateral Hall cell: **3**, 65-75
Lateral impunity profile: **1**, 105-112
Law of total reflection: **9**, 72-79
Layer thickness control: **9**, 101-107
Layered optical coupler: **10**, 41-47
Layout model: **5**, 103-116
Layout model and design: **2**, 101-113
LED array: **12**, 1-11
Learning vector quantization (LVQ): **3**, 52-64
Level conversion: **4**, 61-72
Lidar measurement method: **6**, 53-64
Light components: **4**, 1-17
Light intensity of arc: **9**, 108-114
Light-emitting device: **4**, 27-36
Linear-nonlinear interface: **10**, 57-66
Liquid crystal: **11**, 1-10
Liquid crystal television: **7**, 41-50
Liquid-crystal display: **8**, 104-114; **10**, 104-112
Lithium niobate: **6**, 76-88
Lithium rechargeable battery: **12**, 88-96
Lock-in amplifier: **4**, 37-42
Logic circuits: **8**, 72-82
Low-transmission state: **6**, 33-42
LSI: **3**, 76-88; **8**, 72-82
Magnetic field: **1**, 32-42
Magneto-optical disk: **7**, 103-112
Main beam: **5**, 1-11
Malfunction: **4**, 86-97
Mapping: **12**, 34-39
Mass reprinting: **4**, 73-85
Melt erasing: **7**, 103-112
Melting point: **7**, 103-112
Memory cells: **4**, 86-97; **11**, 102-107
Memory device testing: **5**, 80-88
Metal nitride-oxide semiconductor (MNOS): **4**, 52-60
Metallic phase duration: **11**, 71-80
Micro-instrument: **1**, 32-42
Microcrystallization temperature: **2**, 79-89
Microlens: **11**, 1-10
Micromachine: **11**, 51-61
Microvoids: **2**, 79-89
Microwave frequency: **3**, 109-116
Microwave heating equipment: **9**, 80-90
Microwaves: **5**, 54-66; **8**, 83-94; **9**, 14-24, 63-71
Millimeter waves: **9**, 14-24
Millimeter-wave integrated circuits: **7**, 11-18
Mini-supercomputer: **6**, 53-64
Mirror-type modulation: **8**, 32-43
MNOS: **10**, 93-103
Mode locker: **5**, 12-24
Mode-locking: **5**, 12-24
Modulation doping: **6**, 13-23
Moisture content: **9**, 63-71
Mooney-Rivlin equation: **1**, 96-104
MQW layers: **6**, 24-32
Multicolor display: **10**, 67-74
Multilayered structure: **10**, 57-66
Multiple quantum barrier: **6**, 43-52
Multiple quantum well: **9**, 101-107; **11**, 42-50
Multiquantum well laser: **6**, 13-23
Multisegmentation method: **10**, 57-66
NAND: **10**, 93-103

Narrow noise band width: **3**, 41-51
Nd:YAG: **6**, 1-12
Network analyzer: **2**, 1-11
Neural chip: **2**, 44-60
Neural network: **2**, 44-60; **3**, 89-96; **11**, 11-19
Neurocomputing: **2**, 28-43; **11**, 11-19
Noise margin: **11**, 102-107
Nonaqueous electrolyte gel: **12**, 88-96
Nondegeneracy: **7**, 68-74
Nonlinearity: **2**, 1-11; **4**, 18-62
Nonlinear devices: **6**, 89-100
Nonlinear figure of merit: **12**, 21-33
Nonlinear integrated optics: **1**, 1-10
Nonlinear optical waveguide: **5**, 44-53
Nonlinear optics: **3**, 20-26; **12**, 40-49
Nonlinear refractive index: **10**, 57-66
Nonlinear waveguide analysis: **1**, 1-10
Nonvolatile semiconductor memory device: **4**, 52-60
NTL (Non-threshold logic): **8**, 72-82
Numerical analysis: **3**, 1-8
n-type doping: **8**, 95-103
Omnidirectional measurement: **3**, 65-75
On-resistance: **8**, 63-71; **10**, 75-83
One-chip integration divider architecture: **12**, 57-66
OP-AMP: **4**, 107-118; **8**, 44-53
Open arc: **9**, 108-114
Open structure: **10**, 1-11
Open-type axially symmetric waveguides: **12**, 34-39
Operation feeling: **1**, 96-104
Optical absorption characteristic: **8**, 95-103
Optical amplifier: **6**, 24-32; **8**, 1-13; **8**, 14-22
Optical beam scanning: **5**, 1-11
Optical bistability and feedback: **10**, 48-56
Optical buffer memory: **10**, 27-40
Optical bus: **11**, 32-41
Optical CT: **4**, 1-17
Optical communication: **10**, 12-26
Optical computing: **2**, 28-43
Optical detection: **3**, 20-26
Optical encoder: **1**, 56-63
Optical excitation: **6**, 43-52
Optical fiber cable: **3**, 27-40
Optical fiber cable transfer splicing systems: **4**, 43-51
Optical fiber communication: **3**, 1-8; **7**, 1-10
Optical fiber switch: **11**, 1-10
Optical field expression: **1**, 1-10
Optical heterodyne sensors: **8**, 23-31
Optical imaging: **4**, 37-42
Optical information processing: **6**, 33-42; **10**, 48-56
Optical integrated circuit: **12**, 12-20; **12**, 40-49
Optical interconnection: **11**, 20-31
Optical interruption: **3**, 27-40
Optical Kerr effect: **7**, 1-10
Optical link: **11**, 32-41
Optical logic operation: **6**, 33-42
Optical modulator: **3**, 9-19; **6**, 76-88; **12**, 12-20
Optical operations: **10**, 12-26
Optical parallel transportation: **12**, 1-11
Optical pickup: **7**, 103-112
Optical postcard: **4**, 73-85
Optical pulse synthesizer: **5**, 12-24
Optical self-routing circuit: **10**, 27-40
Optical sheet memory: **4**, 73-85
Optical soliton transmission: **8**, 1-13
Optical switch: **11**, 42-50; **12**, 50-56
Optical switch-off phenomenon: **4**, 37-42
Optical switching devices: **11**, 20-31
Optical thickness monitoring: **2**, 12-19
Optical transfer splicing system: **3**, 27-40
Optical waveguide: **9**, 54-62; **10**, 41-47; **12**, 40-49
Optoelectric integrated circuit: **10**, 48-56; **11**, 11-19
Overshoot: **1**, 77-85
Oxidation process: **7**, 60-67
Package: **11**, 71-80; **11**, 81-90
Paired-associate problem: **3**, 89-96
Paper battery: **12**, 88-96
Parallel divider: **12**, 57-66
Parallel processing: **2**, 28-43; **10**, 12-26
Parallel processor: **3**, 76-88
Paschen curve: **11**, 71-80
PD array: **12**, 1-11
Performance evaluation: **5**, 103-116
Periodic structure: **7**, 32-40; **9**, 80-90
Periodic waveguide: **7**, 92-102
Phase noise: **2**, 1-11
Phase-locked loop (PLL): **3**, 41-51
Phase-splitter circuits: **1**, 11-20
Photo-CVD method: **7**, 84-91
Photoconductive film: **8**, 44-53
Photodetector: **3**, 20-26
Photodetector: **10**, 41-47
Photodiode: **1**, 56-63
Photoluminescence intensity: **4**, 27-36
Photonic switching: **10**, 27-40
Photosensor: **1**, 56-63
Phototransistor: **11**, 42-50
Picosecond/femtosecond: **5**, 12-24
Picture and sound information: **4**, 73-85
Piezoelectric thin film: **12**, 21-33
Planarization: **2**, 44-60
Planer transmission lines: **8**, 83-94
Plasma hydrogenation process: **7**, 51-59
Plasma-polymerization: **10**, 67-74
Poincaré sphere: **8**, 104-114
Polarization: **2**, 90-100
Polarization control: **6**, 1-12
Polarization conversion: **9**, 34-43
Polarization interferometer: **8**, 23-31
Polyaniline: **12**, 88-96
Polycrystalline silicon devices: **7**, 51-59

Porous structure: **7**, 68-74
Power dividers: **1**, 11-20
Power MOSFET: **8**, 63-71
Power reed switch: **2**, 61-71
Power-on: **8**, 54-62
Predecoder circuit: **3**, 97-108
Preemphasis: **7**, 1-10
Preferential oxidation: **7**, 60-67
Pressure sensors: **1**, 64-76
Program structure: **5**, 80-88
Projection slice: **4**, 1-17
Projection theorem: **4**, 1-17
Propagation characteristics: **1**, 21-31
Propagation operation: **3**, 76-88
Pseudoinverse: **3**, 89-96
Pulse density modulation: **2**, 44-60
p-type semiconductor: **7**, 68-74
p^+pn^+ silicon diodes: **7**, 51-59
Q-switch: **6**, 1-12
Quantum well: **6**, 43-52; **9**, 44-53
Quantum well structures: **2**, 20-27; **4**, 27-36
Quarterwave transformers: **5**, 54-66
Quasi-phase matching: **5**, 44-53; **7**, 32-40
Radiation: **1**, 21-31
Raman spectrum: **8**, 95-103
Ray tracing: **7**, 41-50
Re-routing: **3**, 27-40
Red-shift: **4**, 27-36
Redundancy circuit: **5**, 67-79
Reflection coefficient: **5**, 54-66; **9**, 14-24
Relativistic electron beam: **10**, 1-11
Relaxation oscillation frequency: **6**, 13-23
Remote sensing: **9**, 34-43
Repeater spacing: **6**, 24-32
Reproduction envelope: **11**, 91-101
Resistor: **3**, 109-116
Resolving power: **7**, 32-40
Resonant frequency: **9**, 63-71
Resonators: **8**, 83-94
Response and recovery properties: **11**, 1-10
Return loss: **9**, 14-24
RIE: **2**, 72-78
Rigorous solution: **5**, 34-43
Rise time: **11**, 62-70
S-parameters: **2**, 1-11
Saturable absorbing medium: **4**, 37-42
Scaled down: **11**, 102-107
Scaling: **12**, 67-76
Scan operation: **3**, 76-88
Scattering: **7**, 19-31; **9**, 25-33
Scattering parameter: **1**, 21-31
Schottky barrier diode: **4**, 86-97; **2**, 72-78
Second harmonic generation: **12**, 40-49
Selective propagation: **3**, 76-88
Self alignment: **8**, 63-71
Self-timed RAM: **12**, 77-87
Semiconductor fabrication: **7**, 75-83
Semiconductor laser: **4**, 37-42
Semiconductor memory system: **5**, 67-79
Semiconductor waveguide: **5**, 1-11
Sense amplifier: **4**, 86-97
Sensor: **2**, 28-43
Sensor fusion: **2**, 28-43
Sharp drop of hydrogen evolution rate: **2**, 79-89
SIMD: **3**, 76-88
Signal processing: **2**, 28-43
Silicon bipolar process: **8**, 44-53
Silicon devices: **1**, 64-76
Silicon dioxide film: **6**, 65-75
Silicon micromachining technology: **1**, 64-76
Silicon oxynitride film: **7**, 84-91
Silicon solar cell: **7**, 84-91
Simulation: **1**, 21-31; **11**, 71-80; **11**, 62-70, 81-90;
Single-gate FET: **1**, 11-20
Single-mode multifiber connector: **3**, 27-40
Single-mode silicon fibers: **8**, 14-22
Smoothing filter: **3**, 41-51
Solid polymer electrolyte: **12**, 88-96
Solid-state laser: **4**, 18-62
Soliton: **4**, 18-62; **7**, 1-10
Sorting circuit: **2**, 101-113
SPL (Super push-pull logic): **8**, 72-82
Space harmonics: **7**, 19-31
Spatial light modulator: **7**, 41-50
Spatial network method: **6**, 89-100
Spectral chirping: **6**, 13-23
Spot size: **5**, 34-43
SRAM: **11**, 102-107; **12**, 77-87
STN-LCD: **8**, 104-114
Stable propagation mode: **10**, 57-66
Stacked magnetic core: **9**, 91-100
Static induction: **10**, 75-83
Stokes parameters: **9**, 34-43
Strip grating: **7**, 19-31
Subbeam: **5**, 1-11
Subscriber lines: **3**, 1-8
Substrate voltage: **8**, 54-62
Superconducting oxide films: **8**, 83-94
Superlattice: **6**, 43-52
Surface acoustic wave: **12**, 21-33
Surface damage: **2**, 72-78
Surface normal device: **11**, 42-50
Surface oxidized layer: **7**, 60-67
Surface potential control of photoconductor: **10**, 84-92
Surface resistance: **7**, 19-31
Surface resistivity: **8**, 83-94
Surface-emitting laser: **2**, 12-19; **10**, 12-26; **11**, 20-31
Surface-operating functional devices: **10**, 12-26
Surface-stabilized ferroelectric liquid crystals: **6**, 33-42

Switched capacitor: **4**, 98-106
System redundancy: **5**, 67-79
Tactile sensor: **2**, 28-43
Tapered waveguide: **5**, 54-66
Temperature coefficient of resistance: **3**, 109-116
Template matching network: **2**, 44-60
Thermal drift: **6**, 76-88
Thermal printing: **6**, 101-111
Thin films: **6**, 65-75
Thin-film magnetic core: **9**, 91-100
Thin-film optical waveguide: **12**, 50-56
Three-dimensional analysis: **1**, 21-31
Three-dimensional magnetic detection: **3**, 65-75
Three-dimensional VLSI: **2**, 101-113
Three-phase shift: **4**, 98-106
Through-hole: **1**, 21-31
Ti:Li-Nb oxide optical modulator and waveguide: **3**, 9-19
Time-domain analysis: **1**, 21-31
Time-domain method: **1**, 21-31
Timing recovery circuit: **3**, 41-51
Transistorized circuit design: **1**, 43-55
Translinear circuit techniques: **3**, 65-75
Transmission-error reduction: **8**, 23-31
Trap energy distribution: **7**, 51-59
Traveling salesman problem: **2**, 44-60
Traveling-wave diode: **3**, 9-19
Tree structure: **3**, 76-88
Tunable carbon dioxide laser: **8**, 32-43
Tungsten: **11**, 71-80
Tunnel oxide layer: **12**, 67-76
Tunnel quantum well: **5**, 25-33
Twin-striped laser: **11**, 32-41
Two-core fibers: **3**, 1-8
Two-mode pull-in technique: **3**, 41-51
U-groove: **8**, 63-71
Ultra-high-speed communications: **8**, 1-13
Ultralow-frequency oscillator: **4**, 98-106; **11**, 62-70
Ultrashort optical pulse: **5**, 12-24
UNIX: **6**, 53-64
Uniformity control: **7**, 75-83
Upconverter: **7**, 32-40
V_{FB} tracer: **4**, 52-60
Vapor-phase axial deposition (VAD): **8**, 14-22
VCR: **11**, 91-101
Vectorial shape functions: **9**, 1-13
Velocity match: **12**, 12-20
Via hole: **1**, 21-31
Vision sensor: **2**, 28-43
VLSI memory device: **5**, 80-88
VLSI neural system: **2**, 44-60
Voltage between contacts: **2**, 61-71
Volume-time complexity: **2**, 101-113
VSTEPs: **10**, 27-40
Wafer-to-wafer temperature uniformity model: **7**, 75-83
Wave-normal rays: **9**, 72-79
Waveguide: **5**, 54-66; **9**, 14-24; **9**, 44-53
Waveguide components: **1**, 1-10
Waveguide filter: **9**, 80-90
Waveguide interconnection: **10**, 41-47
Wavelength conversion: **5**, 44-53
Wavelength-division multiplex: **7**, 1-10
Weighted potential method: **2**, 20-27
Weighted-index method: **5**, 44-53
Winner-take-all network: **2**, 44-60
X-ray diffraction: **8**, 95-103
XPS carrier mobility: **12**, 97-104